



SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/7

Fiddes Door Oil

Revision 43

Revision date 2016-06-22

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

| | |
|--------------|-----------------|
| Product name | Fiddes Door Oil |
| Product code | Hard Wax Oil |

1.2. Relevant identified uses of the substance or mixture and uses advised against

| | |
|-------------|--|
| Product Use | [SU21] Consumer uses: Private households (= general public = consumers); [PC9a] Coatings and paints, thinners, paint removers; [PROC10] Roller application or brushing; [ERC8c] Wide dispersive indoor use resulting in inclusion into or onto a matrix; [AC11] Wood articles; |
| Description | No data is available on this product. |

1.3. Details of the supplier of the safety data sheet

| | |
|---------------------------------------|---|
| Company | Fiddes & Son Ltd |
| Address | Florence Works, Brindley Road, Cardiff, South Glamorgan, CF11 8TX |
| Web | www.fiddes.co.uk |
| Telephone | +44 (0)29 2034 0323 |
| Fax | +44 (0)29 2034 3235 |
| Email | info@fiddes.co.uk |
| Email address of the competent person | info@fiddes.co.uk |

1.4. Emergency telephone number

| | |
|----------------------------|------------------|
| Emergency telephone number | 1-352-323-3500 |
| Company | INFOTRAC 24HR |

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

| | |
|--------------------------------------|---------------------|
| 2.1.1. Classification - 1999/45/EC | R10 Symbols: |
| Main hazards | Flammable. |
| 2.1.2. Classification - EC 1272/2008 | Flam. Liq. 3: H226; |

2.2. Label elements

| | |
|-------------------------------------|--|
| Hazard pictograms | |
| Signal Word | Warning |
| Hazard Statement | Flam. Liq. 3: H226 - Flammable liquid and vapour. |
| Precautionary Statement: Prevention | P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. |

Fiddes Door Oil

Revision 43

Revision date 2016-06-22

2.2. Label elements

| | |
|--------------------------------------|---|
| Precautionary Statement: Response | P262 - Do not get in eyes, on skin, or on clothing. P280 - Wear protective gloves/protective clothing/eye protection/face protection. |
| | P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P370+P378 - In case of fire: Use foam/CO2 to extinguish. |
| | P102 - Keep out of reach of children. P403+P235 - Store in a well-ventilated place. Keep cool. |
| Precautionary Statement: Storage | |
| Precautionary Statement: Disposal | Dispose of this material and its container to hazardous or special waste collection point. |

Further information

| | |
|--|---|
| | This product is classified and labelled according to CLP. The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version. The classification is according to the latest editions of the EU-lists and extended by company literature and data. |
|--|---|

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

| Chemical Name | Index No. | CAS No. | EC No. | REACH Registration Number | Conc. (%w/w) | Classification | M-factor. |
|---|-----------|------------|-----------|---------------------------|--------------|-------------------|-----------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | | 64742-48-9 | 919-857-5 | 01-2119463258-33 | 30 - 40% | Xn; R65 R10-66-67 | |

EC 1272/2008

| Chemical Name | Index No. | CAS No. | EC No. | REACH Registration Number | Conc. (%w/w) | Classification | M-factor. |
|---|-----------|------------|-----------|---------------------------|--------------|---|-----------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | | 64742-48-9 | 919-857-5 | 01-2119463258-33 | 30 - 40% | EUH066; Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H336; | |

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|--------------|---|
| Inhalation | Remove casualty from exposure ensuring one's own safety whilst doing so. |
| Eye contact | Rinse immediately with plenty of water for 15 minutes holding the eyelids open. |
| Skin contact | Wash with soap and water. |
| Ingestion | DO NOT INDUCE VOMITING. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|--------------|-----------------------|
| Inhalation | Headache. |
| Eye contact | Irritating to eyes. |
| Skin contact | Irritating to skin. |
| Ingestion | Harmful if swallowed. |

4.3. Indication of any immediate medical attention and special treatment needed

| | |
|--------------|-------------------------|
| Inhalation | Seek medical attention. |
| Eye contact | Seek medical attention. |
| Skin contact | Seek medical attention. |
| Ingestion | Seek medical attention. |

SECTION 5: Firefighting measures

5.1. Extinguishing media

| | |
|--|---|
| | Use extinguishing media appropriate to the surrounding fire conditions. |
|--|---|

Fiddes Door Oil

Revision 43

Revision date 2016-06-22

5.3. Advice for firefighters

| | |
|--|---|
| | Wear suitable respiratory equipment when necessary. |
|--|---|

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

| | |
|--|---|
| | Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Do not breathe gas/fumes/vapour/spray. |
|--|---|

6.2. Environmental precautions

| | |
|--|---|
| | Avoid release to the environment. Refer to special instructions/Safety data sheets. Do not allow product to enter drains. |
|--|---|

6.3. Methods and material for containment and cleaning up

| | |
|--|---|
| | For small quantities: Clean area thoroughly with detergent. |
|--|---|

6.4. Reference to other sections

| | |
|--|--|
| | See section 2, 3, 8, 13 for further information. |
|--|--|

SECTION 7: Handling and storage

7.1. Precautions for safe handling

| | |
|--|--|
| | Adopt best Manual Handling considerations when handling, carrying and dispensing. Wear suitable gloves. Do not breathe gas/fumes/vapour/spray. |
|--|--|

7.2. Conditions for safe storage, including any incompatibilities

| | |
|--|--|
| | Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed in a cool place. Store at temperatures between 5 °C and 18 °C. |
|--|--|

7.3. Specific end use(s)

| | |
|--|---------------------------------------|
| | No data is available on this product. |
|--|---------------------------------------|

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| | |
|--|--|
| | See section 8.2 for further information. |
|--|--|

8.2. Exposure controls



8.2.1. Appropriate engineering controls

| | |
|--|--|
| | Ensure adequate ventilation of the working area. |
|--|--|

Eye / face protection

| | |
|--|---------------------------|
| | Wear eye/face protection. |
|--|---------------------------|

Skin protection - Handprotection

| | |
|--|----------------------------------|
| | Chemical resistant gloves (PVC). |
|--|----------------------------------|

Skin protection - Other

| | |
|--|------------------------------------|
| | Wear suitable protective clothing. |
|--|------------------------------------|

Respiratory protection

| | |
|--|---|
| | Wear suitable respiratory equipment when necessary. |
|--|---|

8.2.3. Environmental exposure controls

| | |
|--|-----------------------------------|
| | Avoid release to the environment. |
|--|-----------------------------------|

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Fiddes Door Oil

Revision 43

Revision date 2016-06-22

9.1. Information on basic physical and chemical properties

| | |
|----------------------------------|------------------------|
| Appearance | Liquid |
| Colour | Amber |
| Odour | Slight |
| Odour threshold | No data available |
| pH | Not applicable. |
| Melting point | 0 °C |
| Initial boiling point | 155 - 217 °C |
| Flash point | > 43 °C |
| Evaporation rate | Not applicable. |
| Flammability (solid, gas) | No data available |
| Upper Explosive Limit | 6 % |
| Lower Explosive Limit | 0.7 % |
| Vapour pressure | 0.2 Pa |
| Vapour density | No data available |
| Partition coefficient | No data available |
| Autoignition temperature | > 240 °C |
| Viscosity | 40 mPas (Cone & Plate) |
| Explosive properties | Not applicable. |
| Oxidising properties | No data available |
| Solubility | Immiscible in water |

9.2. Other information

| | |
|---|--------------------------|
| Conductivity | No data available |
| Surface tension | No data available |
| Specific gravity | = 0.88 g/cm ³ |
| Gas group | No data available |
| VOC (Volatile organic compounds) | < 500 g/l |

Water solubility

Insoluble.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data is available on this product.

10.4. Conditions to avoid

Heat, sparks and open flames.

10.5. Incompatible materials

Oxidising agents.

10.6. Hazardous decomposition products

Burning produces irritating, toxic and obnoxious fumes.

SECTION 11: Toxicological information

11.1.4. Toxicological Information

Fiddes Door Oil

Revision 43

Revision date 2016-06-22

11.1.4. Toxicological Information

| | | |
|--|---|---------------------------|
| Fiddes Door Oil | Dermal Rat LD50: >5000mg/kg Inhalation Rat LC50/4 h: 8500mg/kg | Oral Rat LD50: >5000mg/kg |
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cylics, <2% aromatics | Inhalation Rat LC50/8500 h: 4 Dermal Rabbit LD50: >5000 | Oral Rat LD50: >5000 |

SECTION 12: Ecological information

12.1. Toxicity

| | | |
|--|--|---------------------------|
| Fiddes Door Oil | Fish LC50/96h: 1000.000000 mg/l Daphnia LC50/48h: >1000mg/l | Algae EC50/72h: >1000mg/l |
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cylics, <2% aromatics | Fish LC50/96h: 1000.000000 mg/l Daphnia LC50/48h: >1000 | Algae EC50/72h: >1000 |

12.2. Persistence and degradability

| | |
|--|---------------------------------------|
| | No data is available on this product. |
|--|---------------------------------------|

12.3. Bioaccumulative potential

| | |
|--|---------------------------------------|
| | No data is available on this product. |
|--|---------------------------------------|

Partition coefficient

| | |
|--|-----------------------------------|
| | Fiddes Door Oil No data available |
|--|-----------------------------------|

12.4. Mobility in soil

| | |
|--|---------------------------------------|
| | No data is available on this product. |
|--|---------------------------------------|

12.5. Results of PBT and vPvB assessment

| | |
|--|---------------------------------------|
| | No data is available on this product. |
|--|---------------------------------------|

12.6. Other adverse effects

| | |
|--|---------------------------------------|
| | No data is available on this product. |
|--|---------------------------------------|

SECTION 13: Disposal considerations

13.1. Waste treatment methods

| | |
|--|--|
| | Dispose of as special waste in compliance with local and national regulations. |
|--|--|

Disposal of packaging

| | |
|--|---|
| | After final product withdrawl, all residues must be removed from containers (drip-free, powder-free or paste-free). Empty containers can be sent for disposal or recycling. |
|--|---|

SECTION 14: Transport information

Hazard pictograms

| | |
|--|---|
| |  |
|--|---|

14.1. UN number

| | |
|--|--------|
| | UN1263 |
|--|--------|

14.2. UN proper shipping name

| | |
|--|-------|
| | PAINT |
|--|-------|

Fiddes Door Oil

Revision 43

Revision date 2016-06-22

14.3. Transport hazard class(es)

| | |
|-----------------|---|
| ADR/RID | 3 |
| Subsidiary risk | - |
| IMDG | 3 |
| Subsidiary risk | - |
| IATA | 3 |
| Subsidiary risk | - |

14.4. Packing group

| | |
|---------------|-----|
| Packing group | III |
|---------------|-----|

14.5. Environmental hazards

| | |
|-----------------------|----|
| Environmental hazards | No |
| Marine pollutant | No |

ADR/RID

| | |
|-----------------|-------|
| Hazard ID | 33 |
| Tunnel Category | (D/E) |

IMDG

| | |
|----------|---------|
| EmS Code | F-E S-E |
|----------|---------|

IATA

| | |
|---------------------------------|-------|
| Packing Instruction (Cargo) | 366 |
| Maximum quantity | 220 L |
| Packing Instruction (Passenger) | 355 |
| Maximum quantity | 60 L |

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

| | |
|-------------|--|
| Regulations | <p>COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.</p> <p>REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.</p> |
|-------------|--|

15.2. Chemical safety assessment

| | |
|--|---------------------------------------|
| | No data is available on this product. |
|--|---------------------------------------|

SECTION 16: Other information

Other information

| | |
|-----------------------------------|---|
| Revision | This document differs from the previous version in the following areas: 2 - Precautionary Statement: Prevention. 2 - Precautionary Statement: Disposal. |
| Text of risk phrases in Section 3 | R10 - Flammable R65 - Harmful: may cause lung damage if swallowed. R66 - Repeated exposure may cause skin dryness or cracking. R67 - Vapours may cause drowsiness and dizziness. |

Fiddes Door Oil

Revision 43

Revision date 2016-06-22

| Other information | |
|---|--|
| Text of Hazard Statements in Section 3 | EUH066 - Repeated exposure may cause skin dryness or cracking. Flam. Liq. 3: H226 - Flammable liquid and vapour. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. STOT SE 3: H336 - May cause drowsiness or dizziness. |
| Product Subcategory | Interior/exterior trim varnishes and woodstains, including opaque woodstains - 400 g/l. |
| Maximum content of VOC | 500 g/l. |
| General information | |
| | This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. |