

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/6

Fiddes Grainfiller

Revision n Revision date 2015-10-02

SECTION 1: Identification of the substance/mixture	re and of the company/undertaking
--	-----------------------------------

1.1. Product identifier

Fiddes Grainfiller **Product name**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Description No data is available on this product.

1.3. Details of the supplier of the safety data sheet

Company Fiddes & Son Ltd

Florence Works, Brindley Road, Cardiff, South Glamorgan, CF11 8TX Address

Web www.fiddes.co.uk +44 (0)29 2034 0323 Telephone Fax +44 (0)29 2034 3235

Email info@fiddes.co.uk Email address of the info@fiddes.co.uk competent person

1.4. Emergency telephone number

1-352-323-3500 **Emergency telephone number**

Company **INFOTRAC**

24HR

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification -Xn; R65 R66-67 1999/45/EC Symbols: Xn: Harmful.

Main hazards Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or

cracking. Vapours may cause drowsiness and dizziness.

2.1.2. Classification - EC

1272/2008

Asp. Tox. 1: H304; STOT SE 3: H336;

2.2. Label elements

Hazard pictograms





Signal Word

Hazard Statement

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Precautionary Statement:

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

Prevention **Precautionary Statement:**

Response

P262 - Do not get in eyes, on skin, or on clothing.

P301+P310 - IF SWALLOWED: IF SWALLOWED: Immediately call a POISON CENTER/doctor/ . P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 - Call a POISON CENTER/doctor/ /if you feel unwell.

Revision 0 Revision date 2015-10-02

2.2. Label elements

	P331 - Do NOT induce vomiting.
Precautionary Statement:	P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
Storage	P405 - Store locked up.
Precautionary Statement:	Dispose of this material and its container to hazardous or special waste collection point.
Disposal	

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration	Conc.	Classification	M-factor.
				Number	(%w/w)		
Hydrocarbons, C9-C11, n-alkanes,		64742-48-9	919-857-5	01-2119463258-33	20 - 30%	Xn; R65 R10-66-67	
isoalkanes, cylics, <2% aromatics							
Ethanol	603-002-00-5	64-17-5	200-578-6		0.5 - 1%	F; R11	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cylics, <2% aromatics		64742-48-9	919-857-5	01-2119463258-33	20 - 30%	EUH066; Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H336;	
Ethanol	603-002-00-5	64-17-5	200-578-6		0.5 - 1%	Flam. Liq. 2: H225;	

SECTION 4: First aid measures

4.1. Description of first aid measures

The Boots paon of mot ala moa	
Inhalation	Remove casualty from exposure ensuring one's own safety whilst doing so.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
Skin contact	Wash with soap and water.
Ingestion	DO NOT INDUCE VOMITING.
4.2. Most important symptoms a	and effects, both acute and delayed
Inhalation	Harmful by inhalation.
Eye contact	Harmful.

Skin contactHarmful in contact with skin.IngestionHarmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Seek medical attention.
Eye contact	Seek medical attention.
Skin contact	Seek medical attention.
Ingestion	Seek medical attention.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Use extinguishing media appropriate to the surrounding fire conditions.

5.2. Special hazards arising from the substance or mixture

Burning produces irritating, toxic and obnoxious fumes.

5.3. Advice for firefighters

Wear suitable respiratory equipment when necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area.




Revision 0 Revision date 2015-10-02

6.2. Environmental precaution	s
	Avoid release to the environment. Refer to special instructions/Safety data sheets. Do not allow product to enter drains.
6.3. Methods and material for	containment and cleaning up
	For small quantities:. Clean area thoroughly with detergent.
6.4. Reference to other section	ns
	See section 2, 3, 8, 13 for further information.
SECTION 7: Handling and	storage
7.1. Precautions for safe hand	ling
	Adopt best Manual Handling considerations when handling, carrying and dispensing.
7.2. Conditions for safe storag	e, including any incompatibilities
	Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed in a cool place. Store at temperatures between 5 °C and 18 °C.
7.3. Specific end use(s)	
	No data is available on this product.
SECTION 8: Exposure conf	trols/personal protection
8.1. Control parameters	
	See section 8.2 for further information.

8.1.1. Exposure Limit Values

Ethanol	WEL 8-hr limit ppm: 1000	WEL 8-hr limit mg/m3: 1920
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:

8.2. Exposure controls



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties



Revision 0
Revision date 2015-10-02

9.1. Information on basic physical and chemical properties

Paste **Appearance** Colour Various Odour Characteristic pН Not applicable. Melting point Not applicable. Initial boiling point No data available Flash point 40 °C No data available **Evaporation rate** Flammability (solid, gas) No data available Vapour density No data available Relative density 2 (H2O = 1 @ 20 °C) Partition coefficient No data available Autoignition temperature No data available Viscosity No data available **Explosive properties** No data available No data available Oxidising properties Solubility Immiscible in water

9.2. Other information

Conductivity
Surface tension
VOC (Volatile organic compounds)
Not applicable.
No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data is available on this product.

10.4. Conditions to avoid

Heat, sparks and open flames.

10.5. Incompatible materials

Oxidising agents.

10.6. Hazardous decomposition products

Burning produces irritating, toxic and obnoxious fumes.

SECTION 11: Toxicological information

11.1.4. Toxicological Information

No data available

SECTION 12: Ecological information

12.1. Toxicity

No data available

12.2. Persistence and degradability

No data is available on this product.

12.3. Bioaccumulative potential



Revision 0
Revision date 2015-10-02

12.3. Bioaccumulative potential	
No data is available on this product.	
Partition coefficient	
	lydrocarbons, C9-C11, n-alkanes, No data available isoalkanes, cylics, <2% aromatics
12.4. Mobility in soil	
No data is available on this product.	
12.5. Results of PBT and vPvB assessment	
No data is available on this product.	
12.6. Other adverse effects	
No data is available on this product.	
SECTION 13: Disposal considerations	
13.1. Waste treatment methods	
Dispose of as special waste in compliance with local	al and national regulations
Disposal of packaging	ai and national regulations.
After final product withdrawl, all residues must be re	emoved from containers (drip free nowder free
or paste-free). Empty containers can be sent for dis	
SECTION 14: Transport information	
Hazard pictograms	
3	
14.1. UN number	
UN1263	
14.2. UN proper shipping name	
PAINT RELATED MATERIAL	
14.3. Transport hazard class(es)	
ADR/RID Subsidiary risk -	
IMDG 3	
Subsidiary risk -	
IATA 3	
Subsidiary risk -	
14.4. Packing group	
Packing group III	
14.5. Environmental hazards	
Environmental hazards No	
Marine pollutant No	
ADR/RID	
Hazard ID 33	
Tunnel Category (D/E)	
IMDG	
EmS Code F-E S-E	



Revision 0
Revision date 2015-10-02

IATA	
Packing Instruction (Cargo)	366
Maximum quantity	220 L
Packing Instruction	355
(Passenger)	
Maximum quantity	60 L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations

COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC. REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

15.2. Chemical safety assessment

No data is available on this product.

SECTION 16: Other information

Other information

Text of risk phrases in	R10 - Flammable
Section 3	R11 - Highly flammable.
	R65 - Harmful: may cause lung damage if swallowed.
	R66 - Repeated exposure may cause skin dryness or cracking.
	R67 - Vapours may cause drowsiness and dizziness.
Text of Hazard Statements in	EUH066 - Repeated exposure may cause skin dryness or cracking.
Section 3	Flam. Liq. 3: H226 - Flammable liquid and vapour.
	Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
	STOT SE 3: H336 - May cause drowsiness or dizziness.
Maximum content of VOC	300 g/l.
General information	
	This information is correct to the best of our knowledge and belief at the date of publication

This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy.

