



SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/7

U.V Exterior Wood Oil

Revision 4

Revision date 2015-10-07

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name U.V Exterior Wood Oil

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use [SU21] Consumer uses: Private households (= general public = consumers); [PC9a] Coatings and paints, thinners, paint removers; [PROC10] Roller application or brushing; [AC11] Wood articles;
Description Interior/exterior trim varnishes and woodstains, including opaque woodstains.

1.3. Details of the supplier of the safety data sheet

Company Fiddes & Son Ltd
Address Florence Works, Brindley Road, Cardiff, South Glamorgan, CF11 8TX
Web www.fiddes.co.uk
Telephone +44 (0)29 2034 0323
Fax +44 (0)29 2034 3235
Email info@fiddes.co.uk
Email address of the competent person info@fiddes.co.uk

1.4. Emergency telephone number

Emergency telephone number 1-352-323-3500
Company INFOTRAC
24HR

Intended use

Treating exterior wood.

Further information

UK emergency number 02920 340323 8am-5pm, NHS direct wales 0845 46 47, NHS England 111.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC
Xn; R65 R10-66-67
Symbols: Xn: Harmful.
Main hazards Flammable. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.
2.1.2. Classification - EC 1272/2008
Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H336;

2.2. Label elements

Hazard pictograms



Signal Word

Danger

U.V Exterior Wood Oil

Revision 4

Revision date 2015-10-07

2.2. Label elements

Hazard Statement	Flam. Liq. 3: H226 - Flammable liquid and vapour. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. STOT SE 3: H336 - May cause drowsiness or dizziness.
Precautionary Statement: Prevention	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	P301+P310 - IF SWALLOWED: IF SWALLOWED: Immediately call a POISON CENTER/doctor/ . P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 - Call a POISON CENTER/doctor/ /if you feel unwell. P331 - Do NOT induce vomiting. P370+P378 - In case of fire: Use dry powder, foam or CO2 to extinguish.
Precautionary Statement: Storage	P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up.
Precautionary Statement: Disposal	Dispose of this material and its container to hazardous or special waste collection point.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		64742-48-9	919-857-5	01-2119463258-33	40 - 50%	Xn; R65 R10-66-67	
Straight run kerosine - solvent naphtha (petroleum), medium aliph.	649-405-00-X	64742-88-7	265-191-7		10 - 20%	Xn; R65	
Ethyl methyl ketone oxime	616-014-00-0	96-29-7	202-496-6		0.5 - 1%	Carc. Cat. 3; R40 Xn; R21 Xi; R41 R43	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		64742-48-9	919-857-5	01-2119463258-33	40 - 50%	EUH066; Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H336;	
Straight run kerosine - solvent naphtha (petroleum), medium aliph.	649-405-00-X	64742-88-7	265-191-7		10 - 20%	Asp. Tox. 1: H304;	
Ethyl methyl ketone oxime	616-014-00-0	96-29-7	202-496-6		0.5 - 1%	Carc. 2: H351; Acute Tox. 4: H312; Eye Dam. 1: H318; Skin Sens. 1: H317;	

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Do not breathe gas/fumes/vapour/spray. Harmful by inhalation. Headache, nausea and vomiting. If breathing is difficult give oxygen.
Eye contact	Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Skin contact	Avoid contact with skin. May cause irritation to skin. May cause sensitisation by skin contact.
Ingestion	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label. Drink 1 to 2 glasses of water. Harmful if swallowed.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Harmful: possible risk of irreversible effects through inhalation.
Eye contact	May cause irritation to eyes.

U.V Exterior Wood Oil

Revision 4

Revision date 2015-10-07

4.2. Most important symptoms and effects, both acute and delayed

Skin contact	May cause sensitisation by skin contact.
Ingestion	Ingestion may cause nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	If you feel unwell, seek medical advice (show the label where possible).
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
Skin contact	Wash off immediately with plenty of soap and water.
Ingestion	DO NOT INDUCE VOMITING. Drink 1 to 2 glasses of water. Transfer to hospital for specialist examination.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Carbon dioxide (CO ₂). Use extinguishing media appropriate to the surrounding fire conditions.
--	--

5.2. Special hazards arising from the substance or mixture

	In case of fire and/or explosion do not breathe fumes. Eliminate all sources of ignition. Evacuate personnel to a safe area.
--	--

5.3. Advice for firefighters

	In case of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus.
--	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Adopt best Manual Handling considerations when handling, carrying and dispensing. Apply a barrier cream before handling the product.
--	--

6.2. Environmental precautions

	Advise local authorities if large spills cannot be contained. Avoid release to the environment. Refer to special instructions/Safety data sheets. Do not allow product to enter drains. Do not allow runoff water to enter sewers or drains. Do not empty into drains; dispose of this material and its container in a safe way.
--	--

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Dispose of this material and its container to hazardous or special waste collection point.
--	---

6.4. Reference to other sections

	Refer to section 8 and 13 for further information.
--	--

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	---

7.2. Conditions for safe storage, including any incompatibilities

	Contact with combustible material may cause fire. Heat, sparks and open flames. Keep away from food, drink and animal feedingstuffs.
--	--

Suitable packaging

	Store in original container.
--	------------------------------

Suitable packaging

	Mild steel containers.
--	------------------------

SECTION 8: Exposure controls/personal protection

8.2. Exposure controls

U.V Exterior Wood Oil

Revision 4

Revision date 2015-10-07

8.2. Exposure controls

	
8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area. Keep containers tightly closed. Keep in a cool, dry, well ventilated area.
8.2.2. Individual protection measures	Avoid contact with eyes and skin. Chemical resistant clothing. Use appropriate personal protective equipment.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Skin protection - Other	Use as appropriate: Barrier cream.
Respiratory protection	For short periods of work a combination of charcoal filter and particulate filter is suitable.
Occupational exposure controls	Appropriate local exhaust ventilation is required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Amber
Odour	Slight
Odour threshold	No data available
pH	Not applicable.
Melting point	No data available
Initial boiling point	No data available
Flash point	43 °C
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Vapour pressure	No data available
Vapour density	No data available
Relative density	No data available
Partition coefficient	Not applicable.
Autoignition temperature	> 200 °C
Viscosity	No data available
Explosive properties	No data available
Oxidising properties	No data available
Solubility	Immiscible in water

9.2. Other information

Conductivity	No data available
Surface tension	No data available
Specific gravity	0.89 g/cm ³
Gas group	Not applicable.
Benzene Content	No data available
Lead content	No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

	Avoid sparks, flames, heat and sources of ignition.
--	---

10.2. Chemical stability

U.V Exterior Wood Oil

Revision 4

Revision date 2015-10-07

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Amines.

10.4. Conditions to avoid

Avoid sparks, flames, heat and sources of ignition.

10.5. Incompatible materials

Acids. Alkalis.

10.6. Hazardous decomposition products

Danger of spontaneous combustion of rags, cloths or inert absorbent soaked in oil. ensure these materials are dealt with properly(see accidental release measures).

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

Coughing, difficulty in breathing and in severe cases, loss of consciousness.

Skin corrosion/irritation

May cause irritation to skin.

Respiratory or skin sensitisation

Inhalation is irritating to the respiratory tract and may cause damage to the central nervous system.

11.1.4. Toxicological Information

No data available

11.1.7. Information on likely routes of exposure

Inhalation. SKIN CONTACT:.

SECTION 12: Ecological information**12.1. Toxicity**

No data available

12.2. Persistence and degradability

No data is available on this product. Not readily biodegradable.

12.3. Bioaccumulative potential

No data is available on this product.

Partition coefficient

U.V Exterior Wood Oil	Not applicable.	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cylics, <2% aromatics	No data available
-----------------------	-----------------	--	-------------------

12.4. Mobility in soil

Do not let product contaminate subsoil.

12.5. Results of PBT and vPvB assessment

No data is available regarding the preparation itself.

SECTION 13: Disposal considerations**Disposal methods**

Dispose of this material and its container to hazardous or special waste collection point. Do not empty into drains; dispose of this material and its container in a safe way.

Disposal of packaging

Dispose of this material and its container to hazardous or special waste collection point.

SECTION 14: Transport information**Hazard pictograms**

U.V Exterior Wood Oil

Revision 4

Revision date 2015-10-07

Hazard pictograms



14.1. UN number

UN1263

14.2. UN proper shipping name

PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR/RID 3

Subsidiary risk -

IMDG 3

Subsidiary risk -

IATA 3

Subsidiary risk -

14.4. Packing group

Packing group III

14.5. Environmental hazards

Environmental hazards No

Marine pollutant No

ADR/RID

Hazard ID 30

Tunnel Category (D/E)

IMDG

EmS Code F-E S-E

IATA

Packing Instruction (Cargo) 366

Maximum quantity 220 L

Packing Instruction (Passenger) 355

Maximum quantity 60 L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations	COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.
-------------	--

15.2. Chemical safety assessment

	A chemical safety assessment has been carried out. Information from the manufacturer of the raw material has not been received regarding Chemical Safety Assessments, Exposure Scenarios or a Chemical Safety Report.
--	---

SECTION 16: Other information

Other information

U.V Exterior Wood Oil

Revision 4

Revision date 2015-10-07

Other information

Revision	<p>This document differs from the previous version in the following areas:.</p> <ul style="list-style-type: none"> 2 - 2.1. Classification of the substance or mixture. 2 - 2.1.2. Classification - EC 1272/2008. 2 - Hazard pictograms. 2 - Signal Word. 2 - Precautionary Statement: Prevention. 2 - Precautionary Statement: Response. 2 - Precautionary Statement: Storage. 2 - Precautionary Statement: Disposal. 9 - 9.1. Information on basic physical and chemical properties (PH). 9 - 9.1. Information on basic physical and chemical properties (Autoignition temperature). 9 - 9.1. Information on basic physical and chemical properties (Vapour pressure). 9 - 9.1. Information on basic physical and chemical properties (Vapour density). 9 - 9.1. Information on basic physical and chemical properties (Odour threshold). 9 - 9.2. Other information (Gas group). 9 - 9.2. Other information (Specific gravity). 12 - 12.1. Toxicity. 15 - Labelling. 15 - Risk phrases.
Text of risk phrases in Section 3	<ul style="list-style-type: none"> R10 - Flammable R21 - Harmful in contact with skin. R40 - Limited evidence of a carcinogenic effect. R41 - Risk of serious damage to eyes. R43 - May cause sensitisation by skin contact. R65 - Harmful: may cause lung damage if swallowed. R66 - Repeated exposure may cause skin dryness or cracking. R67 - Vapours may cause drowsiness and dizziness.
Text of Hazard Statements in Section 3	<ul style="list-style-type: none"> EUH066 - Repeated exposure may cause skin dryness or cracking. Flam. Liq. 3: H226 - Flammable liquid and vapour. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. STOT SE 3: H336 - May cause drowsiness or dizziness. Acute Tox. 4: H312 - Harmful in contact with skin. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Dam. 1: H318 - Causes serious eye damage. Carc. 2: H351 - Suspected of causing cancer .